

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PRO-FIX 10/10 PART B  
PRODUCT CODE: NA

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: BRAMPTON TECHNOLOGY, LTD  
ADDRESS: 55 MASELLI RD, NEWINGTON, CT 06067  
EMERGENCY PHONE: 860-667-7689 INFORMATION PHONE: 860-667-7689  
DATE REVISED:01/01/00 NAME OF PREPARER:NA

SECTION II – HAZARDOUS INGREDIENTS / SARA III INFORMATION

Hazardous Components	Osha PEL	AOGIH TLV	Other Exposure limits	Percent Mixture	CAS #
TRIETHYLENETETRAMINE	Not Established		Not Established	<10	
SUBSTITUTED AMINOPHENOL	Not Established		Not Established	<10	
DIMER/TOFA, REACTION PRODUCTS WITH TETA	Not Established		Not Established	>90	

THIS PRODUCT DOES NOT CONTAIN ANY HAZARDOUS CHEMICALS AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD.

THIS DOCUMENT IS PREPARED PURSUANT TO THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION III – PHYSICAL/ CHEMICAL CHARACTERISTICS

BOILING RANGE: No Data SPECIFIC GRAVITY (H2O=1): .96  
VAPOR DENSITY: No Data EVAPORATION RATE:NA  
COATING VOC: NA REACTIVITY IN WATER: No Data  
MATERIAL VOC: NA MELTING POINT: No Data  
SOLUBILITY IN WATER : Slight  
APPEARANCE AND ODOR: Amber, Ammoniacal, Irritating

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 392° F METHOD USED: Closed cup  
FLAMMABLE LIMITS IN AIR % BY VOLUME – LOWER: Not determined  
UPPER: Not determined  
AUTO IGNITION TEMPERATURE: No Data

EXTINGUISHING MEDIA: DRY CHEMICAL, CO2 FOAM

SPECIAL FIREFIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: May generate irritating combustion products. Sudden reaction and fire may occur if the product is mixed with an oxidizing agent.

PAGE 2 OF 3  
MATERIAL SAFETY DATA SHEET  
SECTION V REACTIVITY DATA

STABILITY: STABLE  
CONDITIONS TO AVOID: NONE

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents, cleaning solutions such as chromerge (sulfuric acid/dichromate)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Oxides of carbon and nitrogen, aldehydes and other organics.

HAZARDOUS POLYMERIZATION: Will not occur by itself but masses combined with epoxy resin cause irreversible polymerization with heat build up.  
CONDITION TO AVOID: Do not expose to flame, fire or excessive heat.

SECTION VI – HEALTH HAZARD DATA

HAZARD: Possible minor skin irritation from prolonged contact.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Sensitive skin, allergies

CHEMICAL LISTED AS CARCINOGEN	NATIONAL TOXICOLOGY PROGRAM: NO	I.A.R.C. MONOGRAPHS: NO	OSHA: NO
----------------------------------	------------------------------------	----------------------------	----------

EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush immediately with water for at least 15 minutes. Take to a physician for treatment.

Skin: Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if Irritation persists.

Inhalation: NA

Ingestion: Not a probable route of entry

MATERIAL SAFETY DATA SHEET

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store at 0° F for long shelf life

OTHER PRECAUTIONS: Emergency showers and eye wash stations should be readily accessible.

STEPS TO BE TAKEN IN CASE OF RELEASE OR SPILL: Contain with speedy dry and containerize

WASTE DISPOSAL METHODS: Bury as solid waste in an approved landfill or incinerate in accordance with regulations.

SECTION VIII CONTROL MEASURES

RESPIRATORY PROTECTION: Not normally necessary.

VENTILATION: Mechanical suggested

PROTECTIVE GLOVES: Cotton, rubber

EYE PROTECTION: Splash proof

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Clean long sleeve and long leg clothing

WORK / HYGENIC PRACTICES: Normal good industrial housekeeping.

SECTION IX DISCLAIMER

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.